



TECHNICAL BULLETIN

PDR6900NV

PRODUCT: Fire Fine

PRIMARY USE:

Precision one step fining pad for CR39 and Hi Index lenses during ophthalmic manufacturing.

DESCRIPTION:

3" 7 leaf precision graded red European abrasive with compensated backing. Paper side of abrasive is laminated with synthetic rubber, pressure sensitive adhesive for firm, temporary positioning.

LINER:

Bleached, densified kraft paper, clay filled with silicone on one side.

RECOMMENDED TIMES AND PRESSURE:

LOH	1 - 1 1/2 minutes @ .3 to .35 bar
Coburn / Optek	1 – 1 1/2 minutes @ 16-18 psi

TYPICAL PHYSICAL PROPERTIES:

- 1. Thickness:

Pad Material & Adhesive.....	.018"/ .46mm (+/- .001")
Liner.....	4.8 mils (+/- 0.2 mils)

- 2. Peel Adhesion:

PSTC #3	
Linered side.....	80 oz. (+/- 5 oz)

- 3. Dynamic Shear:

(@ 12"/Min.)	
Linered side.....	45 lbs/in. (+/- 6 lbs)

PACKAGING:

Labeled in core with lot number information with plastic protective wrapping.

No warranties are made in this Bulletin. All information, recommendations and descriptive material concerning DAC products are based upon research which is believed to be reliable but shall not constitute a warranty. Accordingly, all DAC products are sold with the understanding that purchaser will be solely responsible for determining the suitability of the materials for any purpose.